

## (12) UK Patent Application (19) GB (11) 2 384 797 (13) A

(43) Date of Printing by UK Office 06.08.2003

(21) Application No 0306600.8

(22) Date of Filing 19.09.2001

(30) Priority Data

(31) 09668440 (32) 22.09.2000 (33) US

(86) International Application Data

PCT/US2001/029321 En 19.09.2001

(87) International Publication Data

WO2002/025052 En 28.03.2002

(51) INT CL<sup>7</sup>

E21B 7/00 21/08 44/00

(52) UK CL (Edition V)

E1F FGL FGM

(56) Documents Cited by ISA

US 4733233 A

US 3963077 A

US 3827511 A

US 3550696 A

US 3517553 A

(58) Field of Search by ISA

Other: U.S.:175/25,24,48,57

(71) Applicant(s)

Varco Shaffer Inc

(Incorporated in USA - Texas)

12950 W Little York Road, Houston,  
TX 77040, United States of America

(74) Agent and/or Address for Service

Forrester Ketley & Co

Forrester House, 52 Bounds Green Road,  
LONDON, N11 2EY, United Kingdom

(72) Inventor(s)


Hubert L Elkins

Mark A Merit

(54) Abstract Title

**Well drilling method and system**

(57) Methods and systems are provided for drilling a wellbore (60) through a subterranean formation using a drilling rig (25) and a drill string (50), whereby the bottom hole pressure while circulating drilling fluid ("ECD") may be substantially maintained when circulation is interrupted or altered, such as when adding a joint of drill pipe to or removing a joint of drill pipe from the drill string. The method includes controllably applying and maintaining a desired variable annulus fluid pressure in the wellbore, and thereafter controllably releasing the pressure from the wellbore (60). In addition, methods and systems are provided for rotating the drill string while trapping, maintaining and/or releasing the wellbore pressure. A substantially constant ECD pressure may be maintained on a formation, thereby facilitating the use of a lower density drilling fluid than may otherwise be required to maintain well control.



GB 2 384 797 A